

Faster 1050 Lift



Standard configuration:
1T +3° _ 300 products



Skudo 1050 Lift




- **Spiral dispenser with lift**
- **Large product capacity in terms of quantity and type**
- **Low energy consumption**
- High impact design, co-ordinating with Hot & Cold machines
- Side-mounted air circulator (patented)
- Internal LED lighting
- Drawers with daisy chain harness

- Compact cooling unit easily extractable (patent pending)
- Door with anti-thief side bar, 3 locking points and re-programmable lock
- Electronics with Flash eprom, can be upgraded without substituting the hardware
- Reflector product photocells detectors
- Fitted for up to 7 drawers
- Prepared for display drawer KIT

General Features		Faster 1050 Lift
Height	mm	1830
Width	mm	1060
Depth	mm	790
Dimensions with door open	mm	1810
Weight	Kg	340
Surfaces and door parts		metal
Antitheft profile		yes
Power	V/Hz	230/50
Consumption EVA-EMP (idle mode)	Wh/h	246
Temperature	C°	snack + drink + food 1T: 3° standard*
Protocol		MDB Executive BDV
Surfaces		RAL 7021 & aluminium

*Other configurations available on request



1) Safety microswitch 2) Motor
3) Encoder 4) Lift card



Stainless steel parts with mechanical end opening

Images and illustrations in this leaflet may not be a true representation of the equipment. FAS advise that the products and specifications could change without prior notice.

Fas International Spa
Via Lago di Vico, 60
36015 Schio - Vicenza - Italy
Tel. +39 0445 502011
Fax +39 0445 502010
info@fas.it
www.fas.it



ISO 14001:2004



UNI EN ISO 9001:2008
N. 9190 FASI



N. IT 8691

